

## SR405G 4G IoT Compact Router

The SMANEX SR405G IoT Compact Router is an entry-level 4G router designed for industrial applications. With its compact design, it features a rugged enclosure and accessories that can be mounted on the wall. The router offers dual SIM functionality, 5 x Giga Ethernet ports, VPN capability, and pre-installed software. The SR405G can be utilized in various IoT applications, such as Smart Energy, Environmental Monitoring, Industrial Automation, Smart City, etc.



## Hardware Spec

Characteristics	CPU	Dual-core ARM A53 CPU1.3Hz
	RAM	1GB
	Flash	32MB
	eMMC	-
Interfaces	Ethernet	1*WAN/LAN, 4*LAN 10/100/1000Mbps
	Serial Port	(RS232*1, RS485*3)/ (RS232*1, RS485*2, DI/O*1) Optional 15KV ESD Protection
	Console	RS232
	USB	1*USB2.0
	Reset Button	1
	SIM	2 Slots (1.8V/3.3V)
	WiFi	WiFi6 IEEE802.11a/b/g/n/ac/ax
	Antenna	3G/4G: SMA*2 5G: SMA*4 WiFi*2 (GPS is optional)
Power	Power Input	DC 5-48V, POE (optional)
	Consumption (operation)	7.84W (3/4G) 8.97W (5G)
	Consumption (stand-by)	319-682 mA@12VDC
Ambient Temperature	Relative humidity	≤ 95% (no condensation)
	Operating Temperature	-40 ~ +75°C
	Storage Temperature	-40 ~ +75°C
Product Appearance	Dimension	143.55*108*49.35mm
	Protection Rating	IP30
	Weight	556g
	Installation	Din-rail

## FEATURES

# Compact Industrial Router

## Software Spec

Network	Connectivity	3G/4G LTE-FDD: B1/B2/B3/B5/B7/B8/B20/B28 LTE-TDD: B34/B38/B39/B40/B41 WCDMA: B1/B2/B5/B8
	WAN	Static IP, DHCP, PPPoE
Network Protocols	IP Routing	Static Router, RIP, OSPF (optional)
	DDNS	DYDNS, CHANGEIP, 88ip, 3322
Security	Firewall	NAT, PAT, DMZ, Port Forwarding, Virtual Server
	VPN	L2TP, OpenVPN, SD-LAN
Reliability	Redundancy	Dual SIM
	Link On-line Detection	Keep Session
		ICMP, Internet Control Message Protocol
Embedded Watch Dog	Hardware Watch Dog	
Industrial Protocol	Collection Protocols	Modbus TCP Master、Modbus RTU Master
	Upload Protocols	Modbus TCP Client、MQTT Client
Development	-	
Management	Configuration	Local or Remote HTTP, HTTPS, Telnet, SSH
		Parameter Backup and Recovery
		SNMP v2c
		Configuration via cloud platform
	Upgrade	Local upgrade
		Remote upgrade via WEB/TFTP/FTP
		Upgrade via cloud server
	Log Management	Local and remote log management
	Reboot	Remote reboot with scheduling
	PING	Internet diagnosis

## FEATURES